




CHANNEL NUT WITH SPRING – FOR USE WITH $1\frac{5}{8}$ " CHANNEL



Part number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With $1\frac{5}{8}$ " Channel
P1006U-1420 SS	$\frac{1}{4}$ " 20	7 (3.2)	P1000, P1100, P2000, P3000
P1008U SS	$\frac{3}{8}$ " 16	10 (4.5)	
P1010U SS	$\frac{1}{2}$ " 13	12 (5.4)	

* All Springs are Pre-Galvanized

The letter "U" in Part number = Sintered type 316 stainless steel

Note

Most fittings, as shown in this catalog are available in stainless steel or aluminum.
It is recommended that stainless steel channel nuts be used with aluminum channels.

MATERIAL

STAINLESS STEEL

Channels: ASTM A 240 (Type 304)

Sintered nuts: ASTM B783 (Type 316N2-33)

Fittings:

ASTM A240 (Type 304) or ASTM A276 (Type 304)

Type 316 stainless also available for most products.

Contact factory for specific material availability.

ALUMINUM

Channels (Extruded): ASTM B221 (Type 6063-T6)

Fittings: ASTM B209 (Type 1100F or Type 5052-H32)

Nuts: ASTM B221 (Type 6063-T5)

Project: _____

Architect / Engineer: _____

Date: _____ Phone: _____

Contractor: _____

Address: _____

Notes 1: _____

Notes 2: _____

Approval Stamp: