




P2260 THRU P2270

Wt/100 pcs: 78 Lbs (35.4 kg)



| Part Number | "A" Degree (rad) | "B" In (mm) |
|-------------|------------------|-------------|
| P2270 | 82½° 1.44 | 3½ 91 |
| P2269 | 75° 1.31 | 3½ 91 |
| P2268 | 67½° 1.18 | 3½ 91 |
| P2267 | 60° 1.05 | 3⅞ 94 |
| P2266 | 52½° 0.92 | 3⅞ 94 |
| P2265 | 45° 0.79 | 3⅞ 94 |
| P2264 | 37½° 0.65 | 3⅞ 94 |
| P2263 | 30° 0.52 | 3⅞ 94 |
| P2262 | 22½° 0.39 | 3¾ 95 |
| P2261 | 15° 0.26 | 3¾ 95 |
| P2260 | 7½° 0.13 | 3¾ 95 |

Standard Dimensions for 1½" (41mm) width series channel fittings (Unless Otherwise Shown on Drawing)

Hole Diameter: 9/16" (14mm); Hole Spacing - From End: 13/16" (21mm); Hole Spacing - On Center: 1 7/8" (48mm); Width: 1½" (41mm); Thickness: 1/4" (6mm)

MATERIAL

Fittings, unless noted, are made from hot-rolled, pickled and oiled steel plates, strip or coil, and conform to ASTM specifications A575, A576, A635, or A36. The fitting steel also meets the physical requirements of ASTM A1011 SS GR 33. The pickling of the steel produces a smooth surface free from scale.

Many fittings are also available in stainless steel, aluminum and fiberglass. Consult factory for ordering information.

FINISHES

Fittings are available in:

Perma-Green III (GR),

Electro-galvanized (EG), conforming to ASTM B633 Type III SC1;

Hot-dipped galvanized (HG), conforming to ASTM A123 or A153 and

Plain (PL).

Project: _____

Architect / Engineer: _____

Date: _____ Phone: _____

Contractor: _____

Address: _____

Notes 1: _____

Notes 2: _____

Approval Stamp: