




CHANNEL NUT WITHOUT SPRING



| Part Number | Nut Size Thread | Wt/100 pcs Lbs (kg) | Use With |
|-------------|-----------------|---------------------|-----------------------|
| P4012 | 5/8" -11 | 11 (5.0) | P3300, P4000 P4100 |
| P4023 | 3/4" -10 | 11 (5.0) | |

MATERIAL

Unistrut channel nuts are manufactured from mild steel bars, and after machining operations are completed, they are case hardened, assuring positive biting action into the inturred edge of the Unistrut channel.

| Bolt Size | Channel Nut ASTM |
|--------------------|----------------------|
| 1/4" & 5/16" | A1011 SS GR45 |
| 3/8", 7/16" & 1/2" | A576 GR1015 Modified |
| 5/8" & 3/4" | A36 or A675 GR60 |
| 7/8" | A36 |

FINISHES

Nuts, bolts and washers are electro-galvanized (EG), ASTM B633 Type III SC1 finish, unless otherwise noted.

Many hardware items are also available in stainless steel. Consult factory for ordering information.

Project: _____

Approval Stamp: _____

Architect / Engineer: _____

Date: _____ Phone: _____

Contractor: _____

Address: _____

Notes 1: _____

Notes 2: _____