


**CHANNEL NUT WITH SPRING**

Part Number	Nut Size Thread	Wt/100 pcs Lbs (kg)	Use With
P5506-0832	#8 -32	7 (3.2)	P5500
P5506-1024	#10 -24	7 (3.2)	
P5506-1420	¼" -20	7 (3.2)	
P5507	5/16" -18	6 (2.7)	
P5508	3/8" -16	10 (4.5)	
P5509	7/16" -14	10 (4.5)	
P5510	½" -13	12 (5.4)	

**MATERIAL**

Unistrut channel nuts are manufactured from mild steel bars, and after machining operations are completed, they are case hardened, assuring positive biting action into the inturned edge of the Unistrut channel.

Bolt Size	Channel Nut ASTM
1/4" & 5/16"	A1011 SS GR45
3/8", 7/16" & 1/2"	A576 GR1015 Modified
5/8" & 3/4"	A36 or A675 GR60
7/8"	A36

**FINISHES**

Nuts, bolts and washers are electro-galvanized (EG), ASTM B633 Type III SC1 finish, unless otherwise noted.

Many hardware items are also available in stainless steel. Consult factory for ordering information.

**Project:** \_\_\_\_\_

**Approval Stamp:** \_\_\_\_\_

**Architect / Engineer:** \_\_\_\_\_

**Date:** \_\_\_\_\_ **Phone:** \_\_\_\_\_

**Contractor:** \_\_\_\_\_

**Address:** \_\_\_\_\_

**Notes 1:** \_\_\_\_\_

**Notes 2:** \_\_\_\_\_