



CN-04 TO CN34

CUSH-A-NATOR® STANDARD

HN-04 TO HN34


CUSH-A-NATOR® "COOL BLUE", HIGH TEMP.

Patent D702113



Cush-A-Nator
"Cool Blue"

Cush-A-Nator
Standard



Features

1 Thumb Drive

The Cush-A-Nator® has the exclusive "Thumb Drive" that provides the installer a gripping point to easily open the cushion with the help of leverage tabs and a living hinge. Easy and effortlessly to install.

Self-Alignment

2 Cushion can be opened and placed over the pipe or tube and rotated into place while on the channel and automatically aligned with the channel opening ready for clamping. No more pre-installing cushions or awkward installation. Cushion replacement has been made simple and easy.

3 Pressure Control

The Cush-A-Nator® cushion has a built in squeeze control as part of the cushion design. The side opening and the squeeze control tab provides evenly distributed pressure around the tube or pipe.

4 Complete Clamping Unit



The Cush-A-Nator® is the only strut mounted cushion that is mechanically connected to the supporting steel clamp because the bolt passes through the squeeze control tab forming the single unit connection. This design helps prevent the cushion from excess vibration by being attached directly to the clamp.

MATERIAL

The Cush-A-Nator cushion is manufactured in the United States and made from a new incredibly durable thermoplastic rubber that resists high heat and provides longer life against vibration fatigue. The Cush-A-Nator is made from a proprietary thermoplastic vulcanized material cross-linked with high perfor-

mance rubber and thermoplastic elastomers, which produces the highest operating temperature range in the industry.

<p>Project: 1 ~~~~~</p> <p>Architect / Engineer: 2 ~~~~~</p> <p>Date: 3 ~~~~~ Phone: 4 ~~~~~</p> <p>Contractor: 5 ~~~~~</p> <p>Address: 6 ~~~~~</p> <p>~~~~~</p> <p>Notes 1: 7 ~~~~~</p> <p>~~~~~</p> <p>Notes 2: 8 ~~~~~</p> <p>~~~~~</p>	<p>Approval Stamp:</p>
---	---



Cush-A-Nator® standard is made from our reliable thermoplastic elastomer that has an operating range of -50°F to 275°F (-45°C to 135°C), but provides the features of the new design.

Cush-A-Nator® "Cool Blue" has service temperatures of -65°F to 340°F (-53°C to 170°C).

Cush-A-Nator® Standard - Tube					
Part No.	O.D. Tube Size	Dimensions (inches)			
		A	B	C	D
CN04	1/4"	0.25	0.62	0.27	0.98
CN06	3/8"	0.37	0.82	0.33	1.13
CN08	1/2"	0.50	0.94	0.40	1.34
CN10	5/8"	0.62	1.06	0.46	1.54
CN12	3/4"	0.75	1.20	0.52	1.68
CN14	7/8"	0.87	1.31	0.58	1.82
CN16	1"	1.00	1.44	0.65	1.95
CN18	1 1/8"	1.12	1.57	0.70	2.08
CN22	1 3/8"	1.37	1.82	0.83	2.34
CN24	1 1/2"	1.50	1.95	0.90	2.47
CN26	1 5/8"	1.62	2.07	0.96	2.60
CN34	2 1/8"	2.12	2.57	1.27	3.23

Cush-A-Nator® "Cool Blue" - Tube					
Part No.	O.D. Tube Size	Dimensions (inches)			
		A	B	C	D
HT04	1/4"	0.25	0.62	0.27	0.98
HT06	3/8"	0.37	0.82	0.33	1.13
HT08	1/2"	0.50	0.94	0.40	1.34
HT10	5/8"	0.62	1.06	0.46	1.54
HT12	3/4"	0.75	1.20	0.52	1.68
HT14	7/8"	0.87	1.31	0.58	1.82
HT16	1"	1.00	1.44	0.65	1.95
HT18	1 1/8"	1.12	1.57	0.70	2.08
HT22	1 3/8"	1.37	1.82	0.83	2.34
HT24	1 1/2"	1.50	1.95	0.90	2.47
HT26	1 5/8"	1.62	2.07	0.96	2.60
HT34	2 1/8"	2.12	2.57	1.27	3.23